

DESCRIPTION

- The A-FLASH trim is a superior quality PVC extrusion used as a horizontal flashing to ensure proper drainage with Exterior Insulation and Finish Systems.

USE

- The A-FLASH trim is used as a starter track above openings, at terminations or at horizontal junctions and serves as a drip flashing. The trim/flashing ensures the evacuation of water infiltrations towards the exterior of the wall.
- The A-FLASH is used with EPS-GD or GD-Contour panels.

INSTALLATION

- The trim must be incorporated in the Hydroflex membrane appropriate to the specifications and substrate used.
- The A-FLASH may also be mechanically attached using corrosion resistant fasteners.
- Please refer to the technical drawings and the specifications of the different systems for additional information.

Color
White
Length
3,05m (10')
Height
76mm (3")
Available Widths
45mm (1,75") and 51mm (2")

■ Properties
■ Result

APPEARANCE

- White
- Trims may be painted with most exterior grade latex paints. Prior to painting, the trims must be clean, without grease, oil or other bond-inhibiting substances.

This document contains current information on the product. It is only provided as a guide and is subject to modifications at any time without notice. ADEX Systems Inc. reserves the right to make any modification according to technological progress. Specialised designers, architects, engineers or other professionals that choose to make any use of this information bear the complete responsibility, whatever it be, direct or indirect, that could follow from such use. ADEX Systems Inc. does not bear any responsibility that could give way to damages, defaults, defects, deficiencies, prejudices, loss or decrease of profit, be they direct or indirect, resulting from such use of this information by specialised designers, architects, engineers or other professionals. Please refer to www.adex.ca for the latest version of this document.

August 2011