GRAPHEXCOat

Puncture and Bird Resistant Coating System

ADEX GRAPHEXCOat is a highly durable exterior coating system manufactured with **GRAPHENE** technology for repair of and prevention against woodpecker pecking and other point-force impacts.

The application of **ADEX GRAPHEX**COat is suitable over both new and existing EIFS (Exterior Insulation Finish Systems) and resists forces over 9X times the average pecking force of woodpecker strikes (in tests over 300+ consecutive strikes).

SUPERIOR DURABILITY.

What is **GRAPHENE**? Simply put, graphene is a thin layer of tightly packed carbon atoms, bonded together in a hexagonal honeycomb pattern... and one of the STRONGEST substances known to science.

The typical woodpecker drums surfaces with an average force of 8
Newtons - and with a maximum striking force of 20 Newtons. **ADEX GRAPHEX**COat was developed and tested using a machine that strikes repetitively at 75 Newtons. That's over 9X times the average striking force with excellent results (no penetration of the lamina after 300 strikes).

In comparison to similar systems available, ADEX testing of **GRAPHEX**COat has shown results of being 3X times stronger than other similar 2-coat rendering systems.



ULTIMATE DESIGN FLEXIBILITY.

The application of **ADEX GRAPHEX**COat is very similar to other ADEX basecoat products, requiring no special tools, meshes, or mixing procedures. Installation easily adapts over all new ADEX systems and repairs all existing types of

damaged stucco walls. As a result, **GRAPHEX**COat is not only the most durable coating for EIFS - it is also the most cost-effective to apply.

WARRANTY.

ADEX GRAPHEXCOat has you protected. The available 10-Year Limited Warranty ensures against both product defects and performance failures.

If the **ADEX GRAPHEX**COat layer is penetrated by a woodpecker (or other type of bird) Adex will cover both the cost of material and labour to repair the damaged area. (*Please refer to warranty details*)





ADEX SYSTEMS 7911 Marco Polo Montreal (Quebec) H1E 1N8

1-866-900-ADEX (2339)

GRAPHEXCOat



PRODUCT CODES:

GRAPHEXCOat-**A**: ADGCA **GRAPHEX**COat-**B**: ADGCB

COVERAGES:

GRAPHEXCOat-A: 8 m² to 10 m²

(85 ft² to 110 ft²)

GRAPHEXCOat-B: 16 m² to 19 m²

 $(175 \text{ ft}^2 \text{ to } 205 \text{ ft}^2)$

MIXING:

GRAPHEXCOat-A and B

Mix 1:1 (by weight) with normal Type-GU
Portland Cement. See **GRAPHEX**COat
technical data sheet for more information.

TEST RESULTS:

PUNCTURE RESISTANCE:

@20 N: no damage after 25,000 strikes

@55 N: 16,945 strikes@75 N: 377 strikes

IMPACT RESISTANCE:

@ 3 Joules = Pass

@ 10 Joules = Pass

WATER VAPOUR PERMEANCE:

103 ng/pa·s·m2

WATER IMPERMEABILITY:

Pass. No water transmission after 2 hrs.

FIRE RESISTANCE:

Meets the requirements of Article 3.1.5.5 of the National Building Code of Canada, 2015. Intertek Design No. ASI/WDEIFS 25-01, tested to CAN/ULC S134 (adex-RS system).

