SAFETY DATA SHEET



Trade name: Prime	ЭХ
-------------------	----

Application / Use: Liquid coat priming agent containing sand.

Manufacturer / Supplier:	adex SYSTEMS HEBERTVILLE-STATION PLANT 67, rue Saint-Paul Hebertville-Station (Quebec) GOW 1TO T (418) 343-2640 F (418) 343-2952 www.adex.ca
--------------------------	---

Emergency phone number: CANUTEC +1 (613) 996-6666

SECTION 2 - HAZARDS IDENTIFICATION

GHS Classification	
Carcinogenicity:	Category 1A
Specific target organ toxicity:	Category 1 - Repeated exposure
Hazard pictogram:	
Signal word: DANGER	2
Hazard statements: H350 H372	
	 Do not handle until all safety precautions have been read and understood. Do not breathe dust, fume, gas, mist, vapours, spray. Wear protective gloves, protective clothing, eye protection, face protection. IF SWALLOWED: Immediately call a Poison Center or doctor or physician. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove any contact lenses, if present and it is easy to do. Continue rinsing. IF exposed or concerned, or if you feel unwell, get medical attention. Store locked up. Protect from sunlight.



SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

DANGEROUS INGREDIENTS	CAS NUMBER	CONCENTRATION (%weight/weight)
Silica - Crystalline, Quartz	14808-60-7	12 - 15
Titanium dioxide	13463-67-7	0 - 15

SECTION 4 - FIRST AID MEASURES

Inhalation: Move to fresh air in case of accidental inhalation of dust. Consult a physician.

- **Skin contact:** Wash with soap and water and remove contaminated clothing. Consult a physician if irritation develops and persists.
- **Eye contact:** Immediately flush eyes with running water for 15 minutes while holding eyelids open. Remove any contact lenses, if present and it is easy to do. If irritation persists, rinse again. Get medical attention.
- **Ingestion:** Do not induce vomiting. Consult a physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

General information:	Water based product. May splatter if temperature exceeds boiling point.
Extinguishing media:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Hazardous combustion products:	Information not available.

Firefighting instructions: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:	Avoid dust generation. All persons dealing with clean-up should wear the appropriate protective equipment.
Environmental precautions:	Avoid discharge into drains, water systems or onto the ground.
Methods and materials for containment and cleaning up:	Prevent further leakage or spillage if it is safe to do so. Pick up with shovel and dispose.



SECTION 7 - HANDLING AND STORAGE

Precautions for safe handling:

Handle in accordance with good industrial hygiene and safety practices. Avoid formation of dust. Wear appropriate protective equipment when working with this product.

Conditions for safe storage:

Keep from freezing. The minimum recommended storage temperature for these materials is 4°C/40°F. Store in a cool and dry place, and out of the sun. Storage above 30°C/85°F is not recommended.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure limits:

NAME	CAS NUMBER	ACGIH TLV	OSHA PEL
Silica - Crystalline, Quartz	14808-60-7	TWA (Respirable fraction): 0.025 mg/m ³	TWA (Total dust): 30 mg/m ³ / %SiO ₂ + 2 TWA (Respirable fraction): 250 mppcf / %SiO ₂ + 5 10 mg/m ³ / %SiO ₂ + 2
Titanium dioxide	13463-67-7	TWA (Total dust): 10 mg/m³	TWA (Total dust): 15 mg/m³

ACGIH: American Conference of Government Industrial Hygienists. OSHA: Occupational Safety & Health Administration. PEL: Permissible Exposure Limits. TLV: Threshold Limits Value. TWA: Time Weighted Average. Mppcf: Millions of Particles Per Cubic Foot of air.

Appropriate engineering controls:

Keep concentration of dust in the air below limits (PEL / TLV). Ensure adequate ventilation, especially in confined areas.

Personal protective equipment:

Skin and body protection Wear protective gloves, protective clothing.

Eye protection Use safety goggles.

Respiratory protection Wear suitable respiratory equipment in presence of dust.



SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Odor : Odor Threshold: pH : Boiling point (°C) : Freezing point (°C) : Flash point: Evaporation rate (n-BuAc = 1) : Flammability (solid, gas): Upper/Lower flammability limits: Auto-ignition temperature: Decomposition temperature:	Viscous liquid Ammonia Not available 8 to 10 100 0 Not available <1 Not available Not available Not available
Vapor pressure :	Not available Not available ≻1
Vapor density (Air = 1) : Density (g/ml) : Partition coefficient	1,3 to 1,5
(n-octanol/water) : Viscosity : Water Solubility (20 °C) :	Not available Not available Soluble

SECTION 10 - STABILITY AND REACTIVITY

Reactivity:	The product is stable and non-reactive under normal conditions of use.
Chemical stability:	The product is stable under the recommended storage and handling conditions prescribed.
Possibility of hazardous reactions:	None known.
Conditions to avoid:	Contact with incompatible materials. Do not freeze or overheat.
Incompatible materials:	Material that reacts with water.
Hazardous decomposition products:	Thermal decomposition can generate irritating and toxic gases.

SECTION 11 - TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation:	May cause irritation to the respiratory tract.
Skin contact:	May cause skin irritation and chemical burn.
Eye contact:	May cause irritation and chemical burn.
Ingestion:	May be harmful if ingested.



Acute toxicity



Silica-Crystalline, Quar (CAS # 14808-60-7)	tz: Is considered a known human carcinogen. IARC carcinogenic classification: Group 1 (carcinogenic to humans). (International Agency for Research on Cancer)
	ACGIH carcinogenic classification: A2 (suspected human carcinogen).
	Also, crystalline silica can cause a lung condition known as silicosis after long term exposure to dusts containing crystalline silica. The use of a correctly fitted NIOSH approved respirator should be used when working with this product.
	IDLH = 50 mg/m ³ (NIOSH Immediately Dangerous to Life or Health concentration)
Titanium dioxide: (CAS # 13463-67-7)	Is considered a suspected carcinogen by advising health agencies. IARC carcinogenic classification: Group 2B (suspected human carcinogen). (International Agency for Research on Cancer) Care should be exercised and the use of a correctly fitted NIOSH approved respirator should be used when working with this product.
	IDLH = 5000 mg/m ³ (NIOSH Immediately Dangerous to Life or Health concentration)

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity:	Not available
Persistence and degradability:	Not available
Bioaccumulative potential:	Not available
Mobility in soil:	Not available
Other adverse effects:	Not available

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste disposal: Dispose of in accordance with applicable local, provincial and federal regulations.

SECTION 14 - TRANSPORT INFORMATION

Land transport -	UN/DOT:	Not regulated
Sea transport -	IMDG:	Not regulated
Air transport -	IATA:	Not regulated



SECTION 15 - REGULATORY INFORMATION

Titanium dioxide

Canada WHMIS 2015 classification: DSL (Domestic substance list):	Carcinogenicity - Category 2 Listed.	
US TSCA Inventory: (Toxic Substances Control Act)	Listed.	
<u>Silica - Crystalline, Quartz</u>		
Canada WHMIS 2015 classification: DSL (Domestic substance list):	Carcinogenicity - Category 1A Listed.	
US OSHA hazards:	Dust containing crystalline silica has been classified as a human lung carcinogen. Listed.	
TSCA Inventory: (Toxic Substances Control Act)		

SECTION 16 - OTHER INFORMATION

The information provided on this SDS is correct to the best of our knowledge. Because some of the information used to prepare this document is derived from information provided from our suppliers, and because we have no control over the conditions of handling and use, we assume no responsibility and disclaim all liability for any harmful effects that may be caused by purchase, resale, use or exposure to our product. Customers and users must comply with all applicable health and safety laws, regulations, and orders. All materials may present unknown hazards and should be used with caution.

Date of preparation: March 26th, 2018

Revision: July 10th, 2019